



SHIFTING THE LIMITS

ACCUPOCKET 150/400 TIG

/ TIG welding goes mobile



/ In addition to mobile electrode welding, mobile TIG welding is now a reality thanks to the AccuPocket 150/400 TIG.

One battery charge is enough for up to 17 minutes of continuous operation at full power (150 A) and the device is fully operational again after approx. 30 minutes of rapid charging. AccuBoost Technology ensures that the power needed for perfect ignition and weld properties is permanently at hand.

Featuring its most robust design yet and weighing just 10.9 kg / 24.03 lb, AccuPocket is the perfect companion for assembly work on construction sites.

AccuPocket can also be used in electrically hazardous areas, such as in boiler welding, as a mains cable is not required.



NEW TIG FEATURES:

PULSE MODE

/ Less heat input in TIG welding, better gap-bridging ability and superb weld seam appearance.

TAC

/ Quick and easy tacking by pulsing arcs.

2-STEP/4-STEP SWITCHOVER

/ The user can switch between 2-step and 4-step mode as needed.

TIG COMFORT STOP

/ Moving the welding torch in a particular way automatically lowers the welding current and prevents an arc break at the end of welding.

UP/DOWN WELDING TORCHES

/ Welding parameters can easily be set directly on the welding torch.

INTEGRAL GAS SOLENOID VALVE

/ Gas is supplied through the integral gas solenoid valve.

HIGH-POWER BATTERY

/ One battery charge allows for the production of remarkably long weld seams.

WELD SEAM LENGTH AT MEDIUM POWER:


315 CM / 124.02 IN



*Material: CrNi
Material thickness: 2 mm / 0.08 in
I: 82 A
Gas: Argon*

WELD SEAM LENGTH AT FULL POWER:

130 CM / 51.18 IN



*Material: CrNi
Material thickness: 6 mm / 0.24 in
I: 150 A
Gas: Argon*

TECHNICAL DATA

Rated battery voltage	52.8 V	
Normal charging current	10 A	
Rapid charging current	18 A	
Battery capacity	396 Wh	
Battery type	Li-ion	
Welding current range	Electrode DC	10 - 140 A
	TIG DC	3 - 150 A
Welding current in hybrid mode, MMA welding		
40°C (104°F)	18% D.C.	140 A
40°C (104°F)	25% D.C.	100 A
40°C (104°F)	100% D.C.	40 A
Welding current in hybrid mode, TIG welding		
40°C (104°F)	25% D.C.	150 A
40°C (104°F)	50% D.C.	100 A
40°C (104°F)	100% D.C.	65 A
Open circuit voltage	90 V	
Reduced open circuit voltage	15 V	
Protection class	IP 23	
Type of cooling	AF	
Mark of conformity	CE, S	
Dimensions (l x w x h)	435 x 160 x 310 mm	
	17.12 x 6.29 x 12.20 in	
Weight	10.9 kg / 24.03 lb	

/ Perfect Welding / Solar Energy / Perfect Charging

WE HAVE THREE DIVISIONS AND ONE PASSION: SHIFTING THE LIMITS OF POSSIBILITY.

/ Whether welding technology, photovoltaics or battery charging technology – our goal is clearly defined: to be the innovation leader. With around 3,000 employees worldwide, we shift the limits of what's possible - our more than 850 active patents are testimony to this. While others progress step by step, we innovate in leaps and bounds. Just as we've always done. The responsible use of our resources forms the basis of our corporate policy.

Further information about all Fronius products and our global sales partners and representatives can be found at www.fronius.com



v02 Feb 2014 EN

Fronius Canada Ltd.
2875 Argentia Road, Units 4,5 & 6
Mississauga, ON L5N 8G6
Canada
Telephone +1 905 288-2100
Fax +1 905 288-2101
sales.canada@fronius.com
www.fronius.ca

Fronius USA LLC
6797 Fronius Drive
Portage, IN 46368
USA
Telephone +1 877 FRONIUS
sales.usa@fronius.com
www.fronius-usa.com

Fronius UK Limited
Maidstone Road, Kingston
Milton Keynes, MK10 0BD
United Kingdom
Telephone +44 1908 512 300
Fax +44 1908 512 329
sales.uk@fronius.com
www.fronius.co.uk

Fronius International GmbH
Froniusplatz 1
4600 Wels
Austria
Telephone +43 7242 241-0
Fax +43 7242 241-953940
sales@fronius.com
www.fronius.com