

bester[®]
by Lincoln Electric

**NEW
SYNERGY**

BESTERMIG RANGE

EASY SETTING FOR PERFECT WELDING



www.lincolnelectric.eu

LINCOLN[®]
ELECTRIC

BESTERMIG RANGE

The All New BesterMIG 200-S and 215-S power sources will shift your perception of welding to a higher level.

- Multiprocess: MIG/MAG, FCAW, MMA and TIG Lift.
- Equipped with SYNERGY based on automatic selection of welding parameters.
- Built-in Arc Force and Anti Sticking devices – improving arc starting and stability, for better weld quality.
- Bright digital display.
- Generator ready.
- Easy polarity change.



Gas CO₂/MIX
Fe Ø 0.6/0.8/1.0 mm



Rutile: Bester 6012, Bester 6013
Basic: Bester 7018
Ø 2.5/3.2/4 mm



Tungsten electrodes
WL 15, WL20
Ø 1.0/1.6/2.0 mm

SYNERGY



EASY SETTING FOR PERFECT WELDING

Synergy is an innovative technology based on automatic selection of welding parameters.

- Forget about choosing the right welding current, wire feed or material thickness settings, synergy does it for you, ensuring perfect welds.
- Synergy minimises the risk of welding defects, guaranteeing superb weld quality and low cost implications.
- Seamless welding – automatic adjustment of parameters saves weld time and increases efficiency.

SYNERGY

BESTERMIG 200-S

- Portable, compact welder
- Perfect solution for hobbyists and DIY-enthusiasts – makes welding faster and more efficient
- Max. spool size: \varnothing 200 mm - 5 kg



MAX. SPOOL SIZE
 \varnothing 200mm
5kg




KG
LOW WEIGHT
11.7 kg



BESTERMIG 215-S

- Enlarged feed spool up to 300mm in diameter and 15kg in weight for a wide range of DIY applications
- Max. spool size: \varnothing 300 mm - 15 kg



MAX. SPOOL SIZE
 \varnothing 300mm
15kg



KG
WEIGHT
27 kg



IN BOTH MODELS, THE PACKAGE INCLUDES:



Mig Gun, EURO –
3 m, 150A@35%
[200A@20%]



Welding cable with
electrode holder – 3 m



Ground cable with
clamp – 3 m



Gas hose – 2 m



2 Rolls
0.6/0.8 and
0.8/1.0 mm



Instruction manual
on USB

SPECIFICATIONS

| Product | Item number | Primary power supply | Fuse | Rated output [A] | | | Welding current range [A] | Feeder type and feeding speed (m/min) | Weight (kg) | Dimensions LxWxH (mm) | Protection class |
|-----------------|-------------|--------------------------|------|------------------|-----|-----|---------------------------|---------------------------------------|-------------|-----------------------|------------------|
| | | | | 100% | 60% | 10% | | | | | |
| BESTERMIG 200-S | B18264-1 | 230V+/-15%/1-Ph/50/60 Hz | 16A | 64 | 82 | 200 | 15-200 | 2R/ 2-13 | 11.7 | 480 x 220 x 305 | IP21S |
| BESTERMIG 215-S | B18266-1 | | | | | | | | | | |

| Product | Processes | | | Display Screen | Types of welding wires | | Feed drive rolls | Max. spool size |
|-----------------|-----------|-----|----------|----------------|------------------------|----------------|------------------|------------------|
| | MIG/MAG | MMA | TIG Lift | | Solid | Self-shielding | | |
| BESTERMIG 200-S | • | • | • | DIGITAL | 0.6 - 1.0 | 0.8 - 1.0 | 2R (ø 30 mm) | ø 200 mm - 5 kg |
| BESTERMIG 215-S | | | | | | | 2R (ø 37 mm) | ø 300 mm - 15 kg |

TIG/MMA GUNS

| | |
|----------------|---|
| W10529-17-4V | TIG Gun WTT2 17 - 4 m with valve |
| E/H-200A-25-3M | Welding cable with electrode holder - 3 m |

ROLL KIT FOR SOLID WIRE

| | | |
|-----------------|-------------|--|
| BESTERMIG 200-S | S33444-20 | Roll V0.6 / V0.8 |
| | S33444-21 | Roll V0.8 / V1.0 (Installed in standard) |
| BESTERMIG 215-S | KP14016-0.8 | Roll V0.6 / V0.8 |
| | KP14016-1.0 | Roll V0.8 / V1.0 (Installed in standard) |

ROLL KIT FOR ALUMINIUM WIRE

| | | |
|-----------------|--------------|------------------|
| BESTERMIG 200-S | S33444-22 | Roll U0.8 / U1.0 |
| BESTERMIG 215-S | KP14016-1.2A | Roll U1.0 / U1.2 |

ROLL KIT FOR CORED WIRE

| | | |
|-----------------|--------------|--------------------|
| BESTERMIG 200-S | S33444-23 | Roll VK0.9 / VK1.1 |
| BESTERMIG 215-S | KP14016-1.1R | Roll VK1.0 / VK1.1 |



DOWNLOAD THE MANUAL

ACCESSORIES

| | | BESTERMIG | |
|------------------|--|-----------|-------|
| | | 200-S | 215-S |
| W10430-15-3M | LGS3 150 MIG gun, gas cooled - 3 m | • | • |
| W10430-15-4M | LGS3 150 MIG gun, gas cooled - 4 m | | • |
| W000010786 | Gas nozzle conical ø12 mm | • | • |
| W000010820 | Contact Tip M6x25mm ECu 0.6 mm | • | • |
| W000010821 | Contact Tip M6x25mm ECu 0.8 mm | • | • |
| WP10440-09 | Contact Tip M6x25mm ECu 0.9 mm | • | • |
| W000010822 | Contact Tip M6x25mm ECu 1.0 mm | • | • |
| WP10440-08A | Contact Tip M6x25mm ALU 0.8 mm | • | • |
| WP10440-10A | Contact Tip M6x25mm ALU 1.0 mm | • | • |
| WP10468 | Protection cap for FCAW-SS welding | • | • |
| WP10419-3M | PTFE liner for Aluminium wire (MIG Gun) | • | • |
| WP10419-4M | PTFE Liner Sprl 4 m Red Alu CuSi 1.0-1.2 | | • |
| R-1019-125-1/08R | Adapter for spool S200 (200 mm) | | • |
| K10158-1 | Adapter for spool type B300 | | • |
| K10158 | Adapter for spool type B300 | | • |
| W10529-17-4V | TIG torch WTT2 17- 4 m with valve | • | • |
| E/H-200A-25-3M | Welding cable with electrode holder - 3 m | • | • |
| W000011139 | KIT (set of welding cables) for MMA process: electrode holder with lead to MMA process - 4 m, work lead with clamp - 4 m | • | • |

CUSTOMER ASSISTANCE POLICY

The business of The Lincoln Electric Company® is manufacturing and selling high quality welding equipment, consumables, and cutting equipment. Our challenge is to meet the needs of our customers and to exceed their expectations. On occasion, purchasers may ask Lincoln Electric for information or advice about their use of our products. Our employees respond to enquiries to the best of their ability based on information provided to them by the customers and the knowledge they may have concerning the application. Our employees, however, are not in a position to verify the information provided or to evaluate the engineering requirements for the particular weldment. Accordingly, Lincoln Electric does not warrant or guarantee or assume any liability with respect to such information or advice. Moreover, the provision of such information or advice does not create, expand, or alter any warranty on our products. Any express or implied warranty that might arise from the information or advice, including any implied warranty of merchantability or any warranty of fitness for any customers' particular purpose is specifically disclaimed.

Lincoln Electric is a responsive manufacturer, but the selection and use of specific products sold by Lincoln Electric is solely within the control of, and remains the sole responsibility of the customer. Many variables beyond the control of Lincoln Electric affect the results obtained in applying these types of fabrication methods and service requirements.

Subject to Change – This information is accurate to the best of our knowledge at the time of printing. Please refer to www.lincolnelectric.eu for any updated information.



www.lincolnelectric.eu

LINCOLN
ELECTRIC